



The DMP 770 and 771 Security Command® keypads provide an attractive, user-friendly control with optional 2-button Panic keys for use with DMP Command Processor™ Panels. Each keypad also provides supervised or unsupervised operation, an easy-to-read 16-character fluorescent blue display, AC LED, backlit keyboard, low profile styling, and four designer colors to compliment a variety of room decors.

## MODEL 770 AND 771 SECURITY COMMAND® KEYPADS

### SYSTEM FEATURES

- 2-button Panic keys for Panic, Emergency, and Fire alerts to the central station
- Supervised and unsupervised operation
- 16-character, alphanumeric fluorescent blue display
- System events shown in plain English
- Four additional protection zones
- SPDT door strike relay - 771 keypad
- Each zone individually programmable
- Back arrow and COMMAND key turns off display
- Requires only 4-wire cable from panel
- Single keypad up to 500' on 22 gauge wire
- AC power LED
- Built-in diagnostics for easy service
- Backlit keyboard with tactile feel
- Audible tone on each keystroke
- Built-in prewarn tone
- Ambush code
- Display time of day
- Display armed zones and areas
- Zone status check
- Turn panel relay outputs on or off
- Change user codes from keypad
- Bypass individual zones
- UL listed

## 2-BUTTON PANIC KEYS

The 770 and 771 keypads allow the top row of keys to be used as 2-button Panic keys. This unique feature lets the user press and hold two keys simultaneously to send a Panic, non-medical Emergency, or Fire report to the central station. A label is provided to identify the correct keys.

## MOUNTING OPTIONS

The 770 and 771 keypads can be mounted several different ways, offering you the flexibility to properly complete an installation. For mounting the keypads on solid or uneven walls, you can use the DMP Model 776 Metal Keypad Backbox. The 776 is 1/2" deep with a baked enamel finish and provides 1/4" wire entry holes on the back and sides for convenient wiring.

For applications where conduit is required to the keypad, use the DMP Model 775 Metal Keypad Backbox. The 775 is 1-1/2" deep with three 1/2" x 3/4" knockouts for connecting conduit.

To provide additional protection for the keypad against tampering or unauthorized use, install the DMP Model 777 Plastic Keypad Cover that provides a wall-mounted clear 1/8" thick polycarbonate housing with lifting cover and integral locking mechanism.

## SUPERVISED AND UNSUPERVISED OPERATION

Both keypads also allow you to set unsupervised addresses and connect multiple keypads to any of the panel's available keypad addresses. This feature greatly expands the number of keypads that can be installed to give users the maximum flexibility in operating their system. The unsupervised operation works on all DMP panels.

## FOUR ADDITIONAL PROTECTION ZONES

The DMP 770 and 771 Security Command® keypads provide four programmable Class B protection zones for connecting devices directly to the keypad. These zones can be individually programmed with any zone type. The 770 and 771 are recommended for supervised operation when devices are connected to their protection zones.

## ADDITIONAL 771 FEATURES

In addition to the 16-character alphanumeric VFD display, 4 protection zones, and panic keys, the 771 also features one Form C (dry contact) relay output. This relay can be used for controlling magnetic locks or electric door strikes on protected doors. These devices connect to the Violet (N/C), Gray (Common), and Orange (N/O) conductors on the harness supplied with the 771 keypad. The relay contacts are rated for 1 Amp at 24 VDC.

## LISTINGS AND APPROVALS

The 770 and 771 Security Command® keypads are listed by UL for use with all DMP Command Processor™ panels. Refer to the appropriate Command Processor™ UL Application Document for complete information.

### SPECIFICATIONS

Operating Voltage	8.5 to 15.0 VDC
Operating Current	
Standby	100mA + 1.6mA per active zone
Alarm	100mA + 2mA per zone in alarm + 20mA with annunciator on
Dimensions	6.8" W X 5.0" H X 1.1" D
Mounting Options	
Colors	White, Ivory, Black, and Red

### PANEL COMPATIBILITY

All DMP Command Processor™ Panels

### ACCESSORIES

- 775 Keypad Conduit Backbox
- 776 Keypad Backbox
- 777 Protective Keypad Cover
- 777G Weatherproof Gasket
- 777S Spacer
- 779 Keypad Deskstand
- 5151 White Keypad Housing
- 5252 Ivory Keypad Housing
- 6161 Black Keypad Housing
- 8181 Red Keypad Housing
- WR-0004 4-Wire Replacement Harness
- WR-0012 12-Wire Replacement Harness
- WR-0512 5 Foot 12-Wire Replacement Harness



800 - 641 - 4282

WWW.DMP.COM

CITYWIDE, NATIONWIDE, WORLDWIDE

2500 N. PARTNERSHIP BLVD., SPRINGFIELD, MISSOURI 65803-8877